

Package ‘gert’

December 4, 2023

Type Package

Title Simple Git Client for R

Version 2.0.1

Description Simple git client for R based on 'libgit2' <<https://libgit2.org>> with support for SSH and HTTPS remotes. All functions in 'gert' use basic R data types (such as vectors and data-frames) for their arguments and return values. User credentials are shared with command line 'git' through the git-credential store and ssh keys stored on disk or ssh-agent.

License MIT + file LICENSE

URL <https://docs.ropensci.org/gert/>
<https://ropensci.r-universe.dev/gert>

BugReports <https://github.com/r-lib/gert/issues>

Imports askpass, credentials (>= 1.2.1), openssl (>= 2.0.3),
rstudioapi (>= 0.11), sys, zip (>= 2.1.0)

Suggests spelling, knitr, rmarkdown, testthat

VignetteBuilder knitr

Encoding UTF-8

RoxygenNote 7.2.3

SystemRequirements libgit2 (>= 1.0): libgit2-devel (rpm) or
libgit2-dev (deb)

Language en-US

NeedsCompilation yes

Author Jeroen Ooms [aut, cre] (<<https://orcid.org/0000-0002-4035-0289>>),
Jennifer Bryan [ctb] (<<https://orcid.org/0000-0002-6983-2759>>)

Maintainer Jeroen Ooms <jeroen@berkeley.edu>

Repository CRAN

Date/Publication 2023-12-04 13:10:05 UTC

R topics documented:

| | |
|---------------------------|-----------|
| git_archive | 2 |
| git_branch | 3 |
| git_checkout_pull_request | 4 |
| git_commit | 4 |
| git_config | 6 |
| git_diff | 8 |
| git_fetch | 9 |
| git_ignore | 11 |
| git_merge | 12 |
| git_open | 13 |
| git_rebase | 14 |
| git_remote | 15 |
| git_repo | 16 |
| git_signature | 17 |
| git_stash | 18 |
| git_submodule_list | 19 |
| git_tag | 20 |
| libgit2_config | 21 |
| user_is_configured | 21 |
| Index | 22 |

git_archive

Git Archive

Description

Exports the files in your repository to a zip file that is returned by the function.

Usage

```
git_archive_zip(file = NULL, repo = ".")
```

Arguments

| | |
|------|--|
| file | name of the output zip file. Default is returned by the function |
| repo | The path to the git repository. If the directory is not a repository, parent directories are considered (see git_find). To disable this search, provide the filepath protected with <code>I()</code> . When using this parameter, always explicitly call by name (i.e. <code>repo = </code>) because future versions of gert may have additional parameters. |

Value

path to the zip file that was created

See Also

Other git: [git_branch\(\)](#), [git_commit\(\)](#), [git_config\(\)](#), [git_diff\(\)](#), [git_fetch\(\)](#), [git_ignore](#), [git_merge\(\)](#), [git_rebase\(\)](#), [git_remote](#), [git_repo](#), [git_signature\(\)](#), [git_stash](#), [git_tag](#)

git_branch

*Git Branch***Description**

Create, list, and checkout branches.

Usage

```
git_branch(repo = ".")
```

```
git_branch_list(local = NULL, repo = ".")
```

```
git_branch_checkout(branch, force = FALSE, orphan = FALSE, repo = ".")
```

```
git_branch_create(branch, ref = "HEAD", checkout = TRUE, repo = ".")
```

```
git_branch_delete(branch, repo = ".")
```

```
git_branch_move(branch, new_branch, force = FALSE, repo = ".")
```

```
git_branch_fast_forward(ref, repo = ".")
```

```
git_branch_set_upstream(upstream, branch = git_branch(repo), repo = ".")
```

```
git_branch_exists(branch, local = TRUE, repo = ".")
```

Arguments

| | |
|------------|--|
| repo | The path to the git repository. If the directory is not a repository, parent directories are considered (see git_find). To disable this search, provide the filepath protected with <code>I()</code> . When using this parameter, always explicitly call by name (i.e. <code>repo = </code>) because future versions of gert may have additional parameters. |
| local | set TRUE to only check for local branches, FALSE to check for remote branches. Use NULL to return all branches. |
| branch | name of branch to check out |
| force | ignore conflicts and overwrite modified files |
| orphan | if branch does not exist, checkout unborn branch |
| ref | string with a branch/tag/commit |
| checkout | move HEAD to the newly created branch |
| new_branch | target name of the branch once the move is performed; this name is validated for consistency. |
| upstream | remote branch from git_branch_list , for example "origin/master" |

See Also

Other git: [git_archive](#), [git_commit\(\)](#), [git_config\(\)](#), [git_diff\(\)](#), [git_fetch\(\)](#), [git_ignore](#), [git_merge\(\)](#), [git_rebase\(\)](#), [git_remote](#), [git_repo](#), [git_signature\(\)](#), [git_stash](#), [git_tag](#)

git_checkout_pull_request

GitHub Wrappers

Description

Fetch and checkout pull requests.

Usage

```
git_checkout_pull_request(pr = 1, remote = NULL, repo = ".")
```

```
git_fetch_pull_requests(pr = "*", remote = NULL, repo = ".")
```

Arguments

| | |
|--------|---|
| pr | number with PR to fetch or check out. Use "*" to fetch all pull requests. |
| remote | Optional. Name of a remote listed in git_remote_list() . If unspecified and the current branch is already tracking branch a remote branch, that remote is honored. Otherwise, defaults to origin. |
| repo | The path to the git repository. If the directory is not a repository, parent directories are considered (see git_find). To disable this search, provide the filepath protected with I() . When using this parameter, always explicitly call by name (i.e. repo =) because future versions of gert may have additional parameters. |

Details

By default `git_fetch_pull_requests` will download all PR branches. To remove these again simply use `git_fetch(prune = TRUE)`.

git_commit

Stage and commit changes

Description

To commit changes, start by *staging* the files to be included in the commit using `git_add()` or `git_rm()`. Use `git_status()` to see an overview of staged and unstaged changes, and finally `git_commit()` creates a new commit with currently staged files.

`git_commit_all()` is a convenience function that automatically stages and commits all modified files. Note that `git_commit_all()` does **not** add new, untracked files to the repository. You need to make an explicit call to `git_add()` to start tracking new files.

`git_log()` shows the most recent commits and `git_ls()` lists all the files that are being tracked in the repository. `git_stat_files()`

Usage

```

git_commit(message, author = NULL, committer = NULL, repo = ".")

git_commit_all(message, author = NULL, committer = NULL, repo = ".")

git_commit_info(ref = "HEAD", repo = ".")

git_commit_id(ref = "HEAD", repo = ".")

git_commit_stats(ref = "HEAD", repo = ".")

git_commit_descendant_of(ancestor, ref = "HEAD", repo = ".")

git_add(files, force = FALSE, repo = ".")

git_rm(files, repo = ".")

git_status(staged = NULL, pathspec = NULL, repo = ".")

git_conflicts(repo = ".")

git_ls(repo = ".", ref = NULL)

git_log(ref = "HEAD", max = 100, after = NULL, repo = ".")

git_stat_files(files, ref = "HEAD", repo = ".")

```

Arguments

| | |
|-----------|---|
| message | a commit message |
| author | A git_signature value, default is git_signature_default() . |
| committer | A git_signature value, default is same as author |
| repo | The path to the git repository. If the directory is not a repository, parent directories are considered (see git_find). To disable this search, provide the filepath protected with I() . When using this parameter, always explicitly call by name (i.e. <code>repo = </code>) because future versions of gert may have additional parameters. |
| ref | revision string with a branch/tag/commit value |
| ancestor | a reference to a potential ancestor commit |
| files | vector of paths relative to the git root directory. Use "." to stage all changed files. |
| force | add files even if in gitignore |
| staged | return only staged (TRUE) or unstaged files (FALSE). Use NULL or NA to show both (default). |
| pathspec | character vector with paths to match |
| max | lookup at most latest n parent commits |
| after | date or timestamp: only include commits starting this date |

Value

- `git_status()`, `git_ls()`: A data frame with one row per file
- `git_log()`: A data frame with one row per commit
- `git_commit()`, `git_commit_all()`: A SHA

See Also

Other git: [git_archive](#), [git_branch\(\)](#), [git_config\(\)](#), [git_diff\(\)](#), [git_fetch\(\)](#), [git_ignore](#), [git_merge\(\)](#), [git_rebase\(\)](#), [git_remote](#), [git_repo](#), [git_signature\(\)](#), [git_stash](#), [git_tag](#)

Examples

```
oldwd <- getwd()
repo <- file.path(tempdir(), "myrepo")
git_init(repo)
setwd(repo)

# Set a user if no default
if(!user_is_configured()){
  git_config_set("user.name", "Jerry")
  git_config_set("user.email", "jerry@gmail.com")
}

writeLines(letters[1:6], "alphabet.txt")
git_status()

git_add("alphabet.txt")
git_status()

git_commit("Start alphabet file")
git_status()

git_ls()

git_log()

cat(letters[7:9], file = "alphabet.txt", sep = "\n", append = TRUE)
git_status()

git_commit_all("Add more letters")

# cleanup
setwd(oldwd)
unlink(repo, recursive = TRUE)
```

Description

Get or set Git options, as `git config` does on the command line. **Global** settings affect all of a user's Git operations (`git config --global`), whereas **local** settings are scoped to a specific repository (`git config --local`). When both exist, local options always win. Four functions address the four possible combinations of getting vs setting and global vs. local.

| | local | global |
|-----|-------------------------------|--------------------------------------|
| get | <code>git_config()</code> | <code>git_config_global()</code> |
| set | <code>git_config_set()</code> | <code>git_config_global_set()</code> |

Usage

```
git_config(repo = ".")

git_config_global()

git_config_set(name, value, repo = ".")

git_config_global_set(name, value)
```

Arguments

| | |
|-------|--|
| repo | The path to the git repository. If the directory is not a repository, parent directories are considered (see git_find). To disable this search, provide the filepath protected with <code>I()</code> . When using this parameter, always explicitly call by name (i.e. <code>repo = </code>) because future versions of gert may have additional parameters. |
| name | Name of the option to set |
| value | Value to set. Must be a string, logical, number or NULL (to unset). |

Value

- `git_config()`: a data.frame of the Git options "in force" in the context of repo, one row per option. The level column reveals whether the option is determined from global or local config.
- `git_config_global()`: a data.frame, as for `git_config()`, except only for global Git options.
- `git_config_set()`, `git_config_global_set()`: The previous value of name in local or global config, respectively. If this option was previously unset, returns NULL. Returns invisibly.

Note

All entries in the name column are automatically normalised to lowercase (see https://libgit2.org/libgit2/#HEAD/type/git_config_entry for details).

See Also

Other git: [git_archive](#), [git_branch\(\)](#), [git_commit\(\)](#), [git_diff\(\)](#), [git_fetch\(\)](#), [git_ignore](#), [git_merge\(\)](#), [git_rebase\(\)](#), [git_remote](#), [git_repo](#), [git_signature\(\)](#), [git_stash](#), [git_tag](#)

Examples

```
# Set and inspect a local, custom Git option
r <- file.path(tempdir(), "gert-demo")
git_init(r)

previous <- git_config_set("aaa.bbb", "ccc", repo = r)
previous
cfg <- git_config(repo = r)
subset(cfg, level == "local")
cfg$value[cfg$name == "aaa.bbb"]

previous <- git_config_set("aaa.bbb", NULL, repo = r)
previous
cfg <- git_config(repo = r)
subset(cfg, level == "local")
cfg$value[cfg$name == "aaa.bbb"]

unlink(r, recursive = TRUE)

## Not run:
# Set global Git options
git_config_global_set("user.name", "Your Name")
git_config_global_set("user.email", "your@email.com")
git_config_global()

## End(Not run)
```

git_diff

Git Diff

Description

View changes in a commit or in the current working directory.

Usage

```
git_diff(ref = NULL, repo = ".")

git_diff_patch(ref = NULL, repo = ".")
```

Arguments

| | |
|------|--|
| ref | a reference such as "HEAD", or a commit id, or NULL to the diff the working directory against the repository index. |
| repo | The path to the git repository. If the directory is not a repository, parent directories are considered (see git_find). To disable this search, provide the filepath protected with <code>I()</code> . When using this parameter, always explicitly call by name (i.e. <code>repo = </code>) because future versions of gert may have additional parameters. |

See Also

Other git: [git_archive](#), [git_branch\(\)](#), [git_commit\(\)](#), [git_config\(\)](#), [git_fetch\(\)](#), [git_ignore](#), [git_merge\(\)](#), [git_rebase\(\)](#), [git_remote](#), [git_repo](#), [git_signature\(\)](#), [git_stash](#), [git_tag](#)

`git_fetch`*Push and pull*

Description

Functions to connect with a git server (remote) to fetch or push changes. The 'credentials' package is used to handle authentication, the [credentials vignette](#) explains the various authentication methods for SSH and HTTPS remotes.

Usage

```
git_fetch(  
  remote = NULL,  
  refspec = NULL,  
  password = askpass,  
  ssh_key = NULL,  
  prune = FALSE,  
  verbose = interactive(),  
  repo = "."  
)
```

```
git_remote_ls(  
  remote = NULL,  
  password = askpass,  
  ssh_key = NULL,  
  verbose = interactive(),  
  repo = "."  
)
```

```
git_push(  
  remote = NULL,  
  refspec = NULL,  
  set_upstream = NULL,  
  password = askpass,  
  ssh_key = NULL,  
  mirror = FALSE,  
  force = FALSE,  
  verbose = interactive(),  
  repo = "."  
)
```

```
git_clone(  
  remote = NULL,  
  refspec = NULL,  
  password = askpass,  
  ssh_key = NULL,  
  mirror = FALSE,  
  force = FALSE,  
  verbose = interactive(),  
  repo = "."  
)
```

```

    url,
    path = NULL,
    branch = NULL,
    password = askpass,
    ssh_key = NULL,
    bare = FALSE,
    mirror = FALSE,
    verbose = interactive()
)

git_pull(remote = NULL, rebase = FALSE, ..., repo = ".")

```

Arguments

| | |
|--------------|--|
| remote | Optional. Name of a remote listed in git_remote_list() . If unspecified and the current branch is already tracking branch a remote branch, that remote is honored. Otherwise, defaults to origin. |
| refspec | string with mapping between remote and local refs. Default uses the default refspec from the remote, which usually fetches all branches. |
| password | a string or a callback function to get passwords for authentication or password protected ssh keys. Defaults to askpass which checks <code>getOption('askpass')</code> . |
| ssh_key | path or object containing your ssh private key. By default we look for keys in ssh-agent and credentials::ssh_key_info . |
| prune | delete tracking branches that no longer exist on the remote, or are not in the refspec (such as pull requests). |
| verbose | display some progress info while downloading |
| repo | The path to the git repository. If the directory is not a repository, parent directories are considered (see git_find). To disable this search, provide the filepath protected with <code>I()</code> . When using this parameter, always explicitly call by name (i.e. <code>repo = </code>) because future versions of gert may have additional parameters. |
| set_upstream | change the branch default upstream to remote. If NULL, this will set the branch upstream only if the push was successful and if the branch does not have an upstream set yet. |
| mirror | use the <code>--mirror</code> flag |
| force | use the <code>--force</code> flag |
| url | remote url. Typically starts with <code>https://github.com/</code> for public repositories, and <code>https://yourname@github.com/</code> or <code>git@github.com/</code> for private repos. You will be prompted for a password or pat when needed. |
| path | Directory of the Git repository to create. |
| branch | name of branch to check out locally |
| bare | use the <code>--bare</code> flag |
| rebase | if TRUE we try to rebase instead of merge local changes. This is not possible in case of conflicts (you will get an error). |
| ... | arguments passed to git_fetch |

Details

Use `git_fetch()` and `git_push()` to sync a local branch with a remote branch. Here `git_pull()` is a wrapper for `git_fetch()` which then tries to **fast-forward** the local branch after fetching.

See Also

Other git: `git_archive`, `git_branch()`, `git_commit()`, `git_config()`, `git_diff()`, `git_ignore`, `git_merge()`, `git_rebase()`, `git_remote`, `git_repo`, `git_signature()`, `git_stash`, `git_tag`

Examples

```
{# Clone a small repository
git_dir <- file.path(tempdir(), 'antiword')
git_clone('https://github.com/ropensci/antiword', git_dir)

# Change into the repo directory
olddir <- getwd()
setwd(git_dir)

# Show some stuff
git_log()
git_branch_list()
git_remote_list()

# Add a file
write.csv(iris, 'iris.csv')
git_add('iris.csv')

# Commit the change
jerry <- git_signature("Jerry", "jerry@hotmail.com")
git_commit('added the iris file', author = jerry)

# Now in the log:
git_log()

# Cleanup
setwd(olddir)
unlink(git_dir, recursive = TRUE)
}
```

git_ignore

Git Ignore

Description

Test if files would be ignored by `.gitignore` rules

Usage

```
git_ignore_path_is_ignored(path, repo = ".")
```

Arguments

| | |
|------|--|
| path | A character vector of paths to test within the repo |
| repo | The path to the git repository. If the directory is not a repository, parent directories are considered (see git_find). To disable this search, provide the filepath protected with <code>I()</code> . When using this parameter, always explicitly call by name (i.e. <code>repo = </code>) because future versions of gert may have additional parameters. |

Value

A logical vector the same length as path, indicating if the paths would be ignored.

See Also

Other git: [git_archive](#), [git_branch\(\)](#), [git_commit\(\)](#), [git_config\(\)](#), [git_diff\(\)](#), [git_fetch\(\)](#), [git_merge\(\)](#), [git_rebase\(\)](#), [git_remote](#), [git_repo](#), [git_signature\(\)](#), [git_stash](#), [git_tag](#)

| | |
|-----------|----------------------|
| git_merge | <i>Merging tools</i> |
|-----------|----------------------|

Description

Use `git_merge` to merge a branch into the current head. Based on how the branches have diverged, the function will select a fast-forward or merge-commit strategy.

Usage

```
git_merge(ref, commit = TRUE, squash = FALSE, repo = ".")
```

```
git_merge_stage_only(ref, squash = FALSE, repo = ".")
```

```
git_merge_find_base(ref, target = "HEAD", repo = ".")
```

```
git_merge_analysis(ref, repo = ".")
```

```
git_merge_abort(repo = ".")
```

Arguments

| | |
|--------|--|
| ref | branch or commit that you want to merge |
| commit | automatically create a merge commit if the merge succeeds without conflicts. Set this to FALSE if you want to customize your commit message/author. |
| squash | omits the second parent from the commit, which make the merge a regular single-parent commit. |
| repo | The path to the git repository. If the directory is not a repository, parent directories are considered (see git_find). To disable this search, provide the filepath protected with <code>I()</code> . When using this parameter, always explicitly call by name (i.e. <code>repo = </code>) because future versions of gert may have additional parameters. |
| target | the branch where you want to merge into. Defaults to current HEAD. |

Details

By default `git_merge` automatically commits the merge commit upon success. However if the merge fails with `merge-conflicts`, or if `commit` is set to `FALSE`, the changes are staged and the repository is put in merging state, and you have to manually run `git_commit` or `git_merge_abort` to proceed.

Other functions are more low-level tools that are used by `git_merge`. `git_merge_find_base` looks up the commit where two branches have diverged (i.e. the youngest common ancestor). The `git_merge_analysis` is used to test if a merge can simply be fast forwarded or not.

The `git_merge_stage_only` function applies and stages changes, without committing or fast-forwarding.

See Also

Other git: [git_archive](#), [git_branch\(\)](#), [git_commit\(\)](#), [git_config\(\)](#), [git_diff\(\)](#), [git_fetch\(\)](#), [git_ignore](#), [git_rebase\(\)](#), [git_remote](#), [git_repo](#), [git_signature\(\)](#), [git_stash](#), [git_tag](#)

| | |
|----------|------------------------------|
| git_open | <i>Open local repository</i> |
|----------|------------------------------|

Description

Returns a pointer to a libgit2 repository object. This function is mainly for internal use; users should simply reference a repository in gert by the path to the directory.

Usage

```
git_open(repo = ".")
```

Arguments

| | |
|------|--|
| repo | The path to the git repository. If the directory is not a repository, parent directories are considered (see git_find). To disable this search, provide the filepath protected with <code>I()</code> . When using this parameter, always explicitly call by name (i.e. <code>repo = </code>) because future versions of gert may have additional parameters. |
|------|--|

Value

an pointer to the libgit2 repository

Examples

```
r <- tempfile(pattern = "gert")
git_init(r)
r_ptr <- git_open(r)
r_ptr
git_open(r_ptr)
git_info(r)
```

```
# cleanup
unlink(r, recursive = TRUE)
```

 git_rebase

Cherry-Pick and Rebase

Description

A cherry-pick applies the changes from a given commit (from another branch) onto the current branch. A rebase resets the branch to the state of another branch (upstream) and then re-applies your local changes by cherry-picking each of your local commits onto the upstream commit history.

Usage

```
git_rebase_list(upstream = NULL, repo = ".")

git_rebase_commit(upstream = NULL, repo = ".")

git_reset_hard(ref = "HEAD", repo = ".")

git_reset_soft(ref = "HEAD", repo = ".")

git_reset_mixed(ref = "HEAD", repo = ".")

git_cherry_pick(commit, repo = ".")

git_ahead_behind(upstream = NULL, ref = "HEAD", repo = ".")
```

Arguments

| | |
|----------|--|
| upstream | branch to which you want to rewind and re-apply your local commits. The default uses the remote upstream branch with the current state on the git server, simulating git_pull . |
| repo | The path to the git repository. If the directory is not a repository, parent directories are considered (see git_find). To disable this search, provide the filepath protected with <code>I()</code> . When using this parameter, always explicitly call by name (i.e. <code>repo = </code>) because future versions of gert may have additional parameters. |
| ref | string with a branch/tag/commit |
| commit | id of the commit to cherry pick |

Details

`git_rebase_list` shows your local commits that are missing from the upstream history, and if they conflict with upstream changes. It does so by performing a rebase dry-run, without committing anything. If there are no conflicts, you can use `git_rebase_commit` to rewind and rebase your branch onto upstream. Gert only support a clean rebase; it never leaves the repository in unfinished "rebasing" state. If conflicts arise, `git_rebase_commit` will raise an error without making changes.

See Also

Other git: [git_archive](#), [git_branch\(\)](#), [git_commit\(\)](#), [git_config\(\)](#), [git_diff\(\)](#), [git_fetch\(\)](#), [git_ignore](#), [git_merge\(\)](#), [git_remote](#), [git_repo](#), [git_signature\(\)](#), [git_stash](#), [git_tag](#)

 git_remote

Git Remotes

Description

List, add, configure, or remove remotes.

Usage

```
git_remote_list(repo = ".")
```

```
git_remote_add(url, name = "origin", refspec = NULL, repo = ".")
```

```
git_remote_remove(remote, repo = ".")
```

```
git_remote_info(remote = NULL, repo = ".")
```

```
git_remote_set_url(url, remote = NULL, repo = ".")
```

```
git_remote_set_pushurl(url, remote = NULL, repo = ".")
```

```
git_remote_refspecs(remote = NULL, repo = ".")
```

Arguments

| | |
|---------|--|
| repo | The path to the git repository. If the directory is not a repository, parent directories are considered (see git_find). To disable this search, provide the filepath protected with <code>I()</code> . When using this parameter, always explicitly call by name (i.e. <code>repo = </code>) because future versions of gert may have additional parameters. |
| url | server url (https or ssh) |
| name | unique name for the new remote |
| refspec | optional string with the remote fetch value |
| remote | name of an existing remote. Default NULL means the remote from the upstream of the current branch. |

See Also

Other git: [git_archive](#), [git_branch\(\)](#), [git_commit\(\)](#), [git_config\(\)](#), [git_diff\(\)](#), [git_fetch\(\)](#), [git_ignore](#), [git_merge\(\)](#), [git_rebase\(\)](#), [git_repo](#), [git_signature\(\)](#), [git_stash](#), [git_tag](#)

`git_repo`*Create or discover a local Git repository*

Description

Use `git_init()` to create a new repository or `git_find()` to discover an existing local repository. `git_info()` shows basic information about a repository, such as the SHA and branch of the current HEAD.

Usage

```
git_init(path = ".", bare = FALSE)
```

```
git_find(path = ".")
```

```
git_info(repo = ".")
```

Arguments

| | |
|-------------------|--|
| <code>path</code> | the location of the git repository, see details. |
| <code>bare</code> | if true, a Git repository without a working directory is created |
| <code>repo</code> | The path to the git repository. If the directory is not a repository, parent directories are considered (see git_find). To disable this search, provide the filepath protected with <code>I()</code> . When using this parameter, always explicitly call by name (i.e. <code>repo = </code>) because future versions of gert may have additional parameters. |

Details

For `git_init()` the `path` parameter sets the directory of the git repository to create. If this directory already exists, it must be empty. If it does not exist, it is created, along with any intermediate directories that don't yet exist. For `git_find()` the `path` arguments specifies the directory at which to start the search for a git repository. If it is not a git repository itself, then its parent directory is consulted, then the parent's parent, and so on.

Value

The path to the Git repository.

See Also

Other git: [git_archive](#), [git_branch\(\)](#), [git_commit\(\)](#), [git_config\(\)](#), [git_diff\(\)](#), [git_fetch\(\)](#), [git_ignore](#), [git_merge\(\)](#), [git_rebase\(\)](#), [git_remote](#), [git_signature\(\)](#), [git_stash](#), [git_tag](#)

Examples

```

# directory does not yet exist
r <- tempfile(pattern = "gert")
git_init(r)
git_find(r)

# create a child directory, then a grandchild, then search
r_grandchild_dir <- file.path(r, "aaa", "bbb")
dir.create(r_grandchild_dir, recursive = TRUE)
git_find(r_grandchild_dir)

# cleanup
unlink(r, recursive = TRUE)

# directory exists but is empty
r <- tempfile(pattern = "gert")
dir.create(r)
git_init(r)
git_find(r)

# cleanup
unlink(r, recursive = TRUE)

```

git_signature

Author Signature

Description

A signature contains the author and timestamp of a commit. Each commit includes a signature of the author and committer (which can be identical).

Usage

```

git_signature_default(repo = ".")

git_signature(name, email, time = NULL)

git_signature_parse(sig)

```

Arguments

| | |
|-------|---|
| repo | The path to the git repository. If the directory is not a repository, parent directories are considered (see git_find). To disable this search, provide the filepath protected with <code>I()</code> . When using this parameter, always explicitly call by name (i.e. <code>repo = </code>) because future versions of <code>gert</code> may have additional parameters. |
| name | Real name of the committer |
| email | Email address of the committer |
| time | timestamp of class <code>POSIXt</code> or <code>NULL</code> |
| sig | string in proper "First Last <your@email.com>" format, see details. |

Details

A signature string has format "Real Name <email> timestamp tzoffset". The timestamp tzoffset piece can be omitted in which case the current local time is used. If not omitted, timestamp must contain the number of seconds since the Unix epoch and tzoffset is the timezone offset in hhmm format (note the lack of a colon separator)

See Also

Other git: [git_archive](#), [git_branch\(\)](#), [git_commit\(\)](#), [git_config\(\)](#), [git_diff\(\)](#), [git_fetch\(\)](#), [git_ignores](#), [git_merge\(\)](#), [git_rebase\(\)](#), [git_remote](#), [git_repo](#), [git_stash](#), [git_tag](#)

Examples

```
# Your default user
try(git_signature_default())

# Specify explicit name and email
git_signature("Some committer", "sarah@gmail.com")

# Create signature for an hour ago
(sig <- git_signature("Han", "han@company.com", Sys.time() - 3600))

# Parse a signature
git_signature_parse(sig)
git_signature_parse("Emma <emma@mu.edu>")
```

git_stash

Stashing changes

Description

Temporary stash away changed from the working directory.

Usage

```
git_stash_save(
  message = "",
  keep_index = FALSE,
  include_untracked = FALSE,
  include_ignored = FALSE,
  repo = "."
)

git_stash_pop(index = 0, repo = ".")

git_stash_drop(index = 0, repo = ".")

git_stash_list(repo = ".")
```

Arguments

| | |
|-------------------|---|
| message | optional message to store the stash |
| keep_index | changes already added to the index are left intact in the working directory |
| include_untracked | untracked files are also stashed and then cleaned up from the working directory |
| include_ignored | ignored files are also stashed and then cleaned up from the working directory |
| repo | The path to the git repository. If the directory is not a repository, parent directories are considered (see git_find). To disable this search, provide the filepath protected with I() . When using this parameter, always explicitly call by name (i.e. <code>repo = </code>) because future versions of gert may have additional parameters. |
| index | The position within the stash list. 0 points to the most recent stashed state. |

See Also

Other git: [git_archive](#), [git_branch\(\)](#), [git_commit\(\)](#), [git_config\(\)](#), [git_diff\(\)](#), [git_fetch\(\)](#), [git_ignore](#), [git_merge\(\)](#), [git_rebase\(\)](#), [git_remote](#), [git_repo](#), [git_signature\(\)](#), [git_tag](#)

git_submodule_list *Submodules*

Description

Interact with submodules in the repository.

Usage

```
git_submodule_list(repo = ".")
git_submodule_info(submodule, repo = ".")
git_submodule_init(submodule, overwrite = FALSE, repo = ".")
git_submodule_set_to(submodule, ref, checkout = TRUE, repo = ".")
git_submodule_add(url, path = basename(url), ref = "HEAD", ..., repo = ".")
git_submodule_fetch(submodule, ..., repo = ".")
```

Arguments

| | |
|------|---|
| repo | The path to the git repository. If the directory is not a repository, parent directories are considered (see git_find). To disable this search, provide the filepath protected with I() . When using this parameter, always explicitly call by name (i.e. <code>repo = </code>) because future versions of gert may have additional parameters. |
|------|---|

| | |
|-----------|---|
| submodule | name of the submodule |
| overwrite | overwrite existing entries |
| ref | a branch or tag or hash with |
| checkout | actually switch the contents of the directory to this commit |
| url | full git url of the submodule |
| path | relative of the submodule |
| ... | extra arguments for git_fetch for authentication things |

 git_tag

Git Tag

Description

Create and list tags.

Usage

```
git_tag_list(match = "*", repo = ".")

git_tag_create(name, message, ref = "HEAD", repo = ".")

git_tag_delete(name, repo = ".")

git_tag_push(name, ..., repo = ".")
```

Arguments

| | |
|---------|--|
| match | pattern to filter tags (use * for wildcard) |
| repo | The path to the git repository. If the directory is not a repository, parent directories are considered (see git_find). To disable this search, provide the filepath protected with <code>I()</code> . When using this parameter, always explicitly call by name (i.e. <code>repo = </code>) because future versions of gert may have additional parameters. |
| name | tag name |
| message | tag message |
| ref | target reference to tag |
| ... | other arguments passed to git_push |

See Also

Other git: [git_archive](#), [git_branch\(\)](#), [git_commit\(\)](#), [git_config\(\)](#), [git_diff\(\)](#), [git_fetch\(\)](#), [git_ignore](#), [git_merge\(\)](#), [git_rebase\(\)](#), [git_remote](#), [git_repo](#), [git_signature\(\)](#), [git_stash](#)

| | |
|----------------|--|
| libgit2_config | <i>Show libgit2 version and capabilities</i> |
|----------------|--|

Description

libgit2_config() reveals which version of libgit2 gert is using and which features are supported, such whether you are able to use ssh remotes.

Usage

```
libgit2_config()
```

Examples

```
libgit2_config()
```

| | |
|--------------------|---|
| user_is_configured | <i>Test if a Git user is configured</i> |
|--------------------|---|

Description

This function exists mostly to guard examples that rely on having a user configured, in order to make commits. user_is_configured() makes no distinction between local or global user config.

Usage

```
user_is_configured(repo = ".")
```

Arguments

repo An optional repo, in the sense of [git_open\(\)](#).

Value

TRUE if user.name and user.email are set locally or globally, FALSE otherwise.

Examples

```
user_is_configured()
```

Index

- * **git**
 - git_archive, 2
 - git_branch, 3
 - git_commit, 4
 - git_config, 6
 - git_diff, 8
 - git_fetch, 9
 - git_ignore, 11
 - git_merge, 12
 - git_rebase, 14
 - git_remote, 15
 - git_repo, 16
 - git_signature, 17
 - git_stash, 18
 - git_tag, 20
- askpass, 10
- credentials::ssh_key_info, 10
- fast-forward, 11
- git_add (git_commit), 4
- git_ahead_behind (git_rebase), 14
- git_archive, 2, 4, 6, 7, 9, 11–13, 15, 16, 18–20
- git_archive_zip (git_archive), 2
- git_branch, 3, 3, 6, 7, 9, 11–13, 15, 16, 18–20
- git_branch_checkout (git_branch), 3
- git_branch_create (git_branch), 3
- git_branch_delete (git_branch), 3
- git_branch_exists (git_branch), 3
- git_branch_fast_forward (git_branch), 3
- git_branch_list, 3
- git_branch_list (git_branch), 3
- git_branch_move (git_branch), 3
- git_branch_set_upstream (git_branch), 3
- git_checkout_pull_request, 4
- git_cherry_pick (git_rebase), 14
- git_clone (git_fetch), 9
- git_commit, 3, 4, 4, 7, 9, 11–13, 15, 16, 18–20
- git_commit_all (git_commit), 4
- git_commit_descendant_of (git_commit), 4
- git_commit_id (git_commit), 4
- git_commit_info (git_commit), 4
- git_commit_stats (git_commit), 4
- git_config, 3, 4, 6, 6, 9, 11–13, 15, 16, 18–20
- git_config_global (git_config), 6
- git_config_global_set (git_config), 6
- git_config_set (git_config), 6
- git_conflicts (git_commit), 4
- git_diff, 3, 4, 6, 7, 8, 11–13, 15, 16, 18–20
- git_diff_patch (git_diff), 8
- git_fetch, 3, 4, 6, 7, 9, 9, 10, 12, 13, 15, 16, 18–20
- git_fetch(), 11
- git_fetch_pull_requests (git_checkout_pull_request), 4
- git_find, 2–5, 7, 8, 10, 12–17, 19, 20
- git_find (git_repo), 16
- git_ignore, 3, 4, 6, 7, 9, 11, 11, 13, 15, 16, 18–20
- git_ignore_path_is_ignored (git_ignore), 11
- git_info (git_repo), 16
- git_init (git_repo), 16
- git_log (git_commit), 4
- git_ls (git_commit), 4
- git_merge, 3, 4, 6, 7, 9, 11, 12, 12, 15, 16, 18–20
- git_merge_abort (git_merge), 12
- git_merge_analysis (git_merge), 12
- git_merge_find_base (git_merge), 12
- git_merge_stage_only (git_merge), 12
- git_open, 13
- git_open(), 21
- git_pull, 14
- git_pull (git_fetch), 9
- git_pull(), 11

- git_push, 20
- git_push (git_fetch), 9
- git_push(), 11
- git_rebase, 3, 4, 6, 7, 9, 11–13, 14, 15, 16, 18–20
- git_rebase_commit (git_rebase), 14
- git_rebase_list (git_rebase), 14
- git_remote, 3, 4, 6, 7, 9, 11–13, 15, 15, 16, 18–20
- git_remote_add (git_remote), 15
- git_remote_info (git_remote), 15
- git_remote_list (git_remote), 15
- git_remote_list(), 4, 10
- git_remote_ls (git_fetch), 9
- git_remote_refsspecs (git_remote), 15
- git_remote_remove (git_remote), 15
- git_remote_set_pushurl (git_remote), 15
- git_remote_set_url (git_remote), 15
- git_repo, 3, 4, 6, 7, 9, 11–13, 15, 16, 18–20
- git_reset_hard (git_rebase), 14
- git_reset_mixed (git_rebase), 14
- git_reset_soft (git_rebase), 14
- git_rm (git_commit), 4
- git_signature, 3–7, 9, 11–13, 15, 16, 17, 19, 20
- git_signature_default (git_signature), 17
- git_signature_default(), 5
- git_signature_parse (git_signature), 17
- git_stash, 3, 4, 6, 7, 9, 11–13, 15, 16, 18, 18, 20
- git_stash_drop (git_stash), 18
- git_stash_list (git_stash), 18
- git_stash_pop (git_stash), 18
- git_stash_save (git_stash), 18
- git_stat_files (git_commit), 4
- git_status (git_commit), 4
- git_submodule_add (git_submodule_list), 19
- git_submodule_fetch (git_submodule_list), 19
- git_submodule_info (git_submodule_list), 19
- git_submodule_init (git_submodule_list), 19
- git_submodule_list, 19
- git_submodule_set_to (git_submodule_list), 19
- git_tag, 3, 4, 6, 7, 9, 11–13, 15, 16, 18, 19, 20
- git_tag_create (git_tag), 20
- git_tag_delete (git_tag), 20
- git_tag_list (git_tag), 20
- git_tag_push (git_tag), 20
- I(), 2–5, 7, 8, 10, 12–17, 19, 20
- libgit2_config, 21
- user_is_configured, 21